For Office Use Only



PRINCE WILLIAM COUNTY
DEPARTMENT OF FIRE AND RESCUE
FIRE MARSHAL'S OFFICE
5 COUNTY COMPLEX CT. SUITE 160
PRINCE WILLIAM, VA 22192
(703) 792-6360 office (703) 792-6492 fax
WWW.PWCGOV.ORG/FIRE

Permit Number:	
Date Issued:	
Expiration Date:	
Required Delivery Date:	

I. <u>Instructional Section</u>

- 1. Please review this application thoroughly, fill out all requested information and submit with all necessary attachments to the Prince William County Fire Marshal's Office at the above address or PWCFMOFOP@pwcgov.org.
- 2. A permit fee of \$357.17 is required at the time of application submittal. Checks can be made out to "Prince William County". Credit card payments are accepted over the phone.
- 3. Prince William County Blasting Permits are good for 6 months from the date of issuance for temporary blasting sites and 12 months for permanent sites.
- 4. A review of this application packet will be conducted and either approved or rejected based on the information provided.
- 5. An onsite inspection will be conducted after packet approval and the permit will be delivered during this inspection if found to meet all requirements.
- 6. You must call Prince William County Communications before and after each blast at (703) 792-6500.
- 7. You must notify the Fire Marshal's Office of each day's proposed blast time no less than 4 hours prior to the proposed blast time at (703) 792-6360.

II. Informational Section

Blasting Company Information	
Name of Blasting Company and Phone Number:	
Address of Blasting Company:	
Emergency Contact Name and Number (after hours):	
Federal Identification Number:	
Job Site Information	

Job Site Name: Job Site Address: GPIN: Name of Onsite Blasting Supervisor: Email Address Blasting Supervisor: Name of Job Site Supervisor: Phone:

The following individuals will be involved in blasting:

Name:	DOB:	Certification #:	Phone #:

The following are identified as potential hazards associated with this job site: (gas lines, overhead power lines, close occupied structures, etc.)				
1.	6.			
2.	7.			
3.	8.			
4.	9.			
5.	10.			

III. Site Plans

Attach a site plan for this worksite. The following information shall be included on the site plan:

- Blast area
- Distance measurements
- Utility locations
- Structures
- Fire Department vehicle access roads (in case of emergencies)
- Fire hydrants if available

IV. List of Required Documents

- ✓ Documentation of \$5,000,000.00 Liability Insurance
- ✓ Copies of Blaster's Background Clearance Card
- ✓ Miss Utility Tickets
- ✓ Site Plan

Carefully review the following:

All blasting in Prince William County is regulated by the following sources:

- Virginia Statewide Fire Prevention Code Chapter 56 (2021 edition)
- NFPA 495 (2018 edition)
- Prince William County Code (Chapter 9.2 Article VII)
- Fire Code Official

Applicable Code Sections:

- *VSFPC 107.2* Operational permits may be required by the fire official as permitted under the SFPC in accordance with Table 107.2.
- VSFPC 107.4 Before a permit is issued the fire official shall make such inspections or tests as are necessary to assure that the use and activities for which application is made comply with the provisions of this code.
- *VSFPC 107.7* Plans approved by the Fire Official are approved with the intent that they comply in all respects to this code. Any omissions or errors on the plans do not relieve the applicant of complying with all applicable requirements of this code.
- *VSFPC 108.4* the Fire Official may revoke a permit or approval issued under the SFPC if conditions of the permit have been violated, or if the approved application, data, or plans contain misrepresentation as to material fact.
- *VSFPC 5601.1.1* in addition to SFPC Chapter 56, NFPA 495 shall govern the manufacture, transportation, storage, sale, handling, and use of explosive materials.
- *VSFPC 5601.2* the storage, possession and use of explosives shall not take place without first applying for and obtaining a permit.
- VSFPC 5601.2.4 and Sec. 9.2-52(PWC Code) before a permit is issued, the applicant shall file with the jurisdiction a corporate surety bond or a public liability insurance policy for the purpose of the payment of all damages to persons or property which arise from, or are caused by, the conduct of any act authorized by the permit upon which any judicial judgment results.
- VSFPC 5601.2.4.1 before approval to do blasting is issued; the applicant for approval shall file a bond or submit a certificate of insurance in such form, amount and coverage as determined by the legal department of the jurisdiction to be adequate in each case to indemnify the jurisdiction against any and all damages arising from permitted blasting.
- *VSFPC 5601.4* persons in charge of blasting shall not be under the influence of alcohol or drugs which impair sensory or motor skills, shall be at least 21 years of age, and possess knowledge of all safety precautions related to the storage, handling or use of explosives, explosive materials, or fireworks.
- *VSFPC 5603.4* accidents involving the use of explosives, explosive materials, or fireworks which result in injuries or property damage, shall be reported to the Fire Code Official and State Fire Marshal.
- *VSFPC 5607.1* blasting operations shall be conducted only by persons certified by the State Fire Marshal Office (SFMO) as a restricted or unrestricted blaster or shall be supervised on-site by a person properly certified by the (SFMO) as a restricted or unrestricted blaster.
- VSFPC 5607.3 blasting that is done in congested areas, near a structure, railway or highway, or any other installation, shall have precautions taken to minimize earth vibrations and air blast effects. Blasting mats or other protective means shall be used to prevent fragments from being thrown.
- *VSFPC 5607.4* surface-blasting operations shall only be conducted during daylight hours between sunrise and sunset. Other blasting shall be performed during daylight hours unless otherwise approved by the fire code official.
- *VSFPC 5607.5* whenever blasting is being conducted in the vicinity of utility lines or rights-of-way, the blaster shall notify the appropriate representatives of the utilities at least <u>24 hours</u> in advance of blasting, specifying the location and intended time of such blasting. Verbal notices shall be confirmed with written notices.

- *VSFPC 5607.15* where a misfire is suspected, all initiating circuits shall be traced, and a search made for unexploded charges. When a misfire is found, the blaster shall provide proper safeguards for excluding all personnel from the blast area. Misfires shall be reported to blasting supervisor immediately. Misfires shall be handled under the direction of the person in charge of the blasting operation in accordance with NFPA 495.
- VSFPC 5607.16 a record of each blast shall be kept and retained for at least five years and shall be available for inspection by the code official. The record shall be in a format selected by the blaster and shall contain the minimum data and information indicated in Form 5607.16.
- NFPA 495 (10.1.5.2) no smoking shall be permitted within 50 feet of any location where explosives are being handled or used.
- NFPA 495 (10.1.5.3) no person within 50 feet of any location where explosives are being handled or used shall carry any matches, open light, or other fire of flame, except for approved devices for lighting safety fuses.
- NFPA 495 (10.1.13) no blasting operation shall be performed in a manner contrary to the instructions of the manufacturer of the explosive materials being used.
- NFPA 495 (10.1.16) persons authorized to prepare explosive charges or to conduct blasting operations shall use every reasonable precaution including, but not limited to, warning signals, flags, barricades, mats, or other equally effective means to ensure the safety of the general public and workers.
- NFPA 495 (10.3.9) no blast shall be fired until the blaster in charge has made certain that all surplus materials are in a safe place, all persons and equipment are at a safe distance or under sufficient cover, and an adequate warning signal has been given.
- NFPA 495 (11.2.1) at all blasting operations, the ground vibration on any axis (particle velocity) shall not exceed the limitations specified in Figure 11.2.1 at the location of any building or structure.
- NFPA 495 (11.3.1) air over pressure due to blasting operations shall not exceed the maximum limit of 133db at the location of any building or structure.
- *NFPA 495(11.4.1)* Flyrock traveling in the air or along the ground shall not be cast from the blast site in an uncontrolled manner that could result in personal injury or property damage.
- NFPA 495(11.4.2) Flyrock shall not be propelled from the blast site onto property not contracted by the blasting operation or onto property for which the owner has not provided a written waiver to the blasting operation.
- *NFPA 495(11.4.3)* where blasting operations do not conform to 11.4.1 and 11.4.2, the AHJ shall require that special precautions be employed to reduce or control Flyrock.
- NFPA 495(11.5.1) gases traveling in the air or through the ground shall be controlled in a manner to prevent injury to persons or damage to property outside the blast area.
- NFPA 495 (11.5.2) to minimize hazardous carbon monoxide exposure produced by blasting, blasters shall be responsible for the following; 1) aware that the lack of ground displacement can prevent venting of blasted materials and result in entrapment of gases, 2) excavate blasted material as soon as practical after blasting, 3) be aware of and look for geologic pathways for gases such as old trenches, horizontal partings, faults, joints, hill-seams, unconsolidated material, water, and voids that would allow movement of gas towards underground enclosed spaces, 4) be aware that blasting near underground enclosed spaces, fractures caused by the detonation can create a pathway for gases, 5) conduct pre-blast surveys to determine any possible problem areas when blasting near inhabited buildings or underground facilities, 6) monitor possible problem areas to determine if any gases have migrated from the blasting operations, 7) if gases are detected, using positive ventilation at inhabited buildings or other facilities from the blasting operations until the gas is removed.

- Sec. 9.2-53(PWC Code) Emergency contact for certified blasters. In addition to the provisions set out in sections 5601.4 of the Fire Prevention Code (2021 edition), persons using explosive materials, within the confines of the county, shall provide emergency contact information to the fire official and update such by the first day of January, April, July, and October. Such information shall include the employer's name, office address, office telephone number, 24-hour emergency contact telephone number, blaster's name, and a 24-hour emergency contact telephone number.
- Sec. 9.2-54(PWC Code) Loss, theft, or unauthorized removal of explosive materials. The loss, theft, or unauthorized removal of explosive materials from a magazine or permitted facility or site shall be reported to the fire official, local law enforcement authorities, and the U.S. Department of Treasury, Bureau of Alcohol, Tobacco Firearms and Explosives (BATF) immediately. Immediate notification to the fire official shall be by telephone or in person followed by a letter giving complete details as to the types, amounts and manufacturer of the explosive materials and other relevant details relating to the loss, theft or unauthorized removal. The letter shall be delivered to the fire official within 24 hours of the verbal notification. Loss of 1.4G (consumer fireworks) do not need to be reported to the BATF.
- Sec. 9.2-55(PWC Code) Improper or unlawful storage of explosive materials. In addition to the provisions in sections 5603.1 of the Fire Prevention Code (2021 Edition), if at any time explosives or explosive materials are found stored in an improper or unlawful manner, immediate notification shall be made to the fire official who shall take all necessary actions to safeguard or dispose of such explosives or explosive materials.
- Pre-blast surveys shall be performed on each structure located within 150ft and any utility well located within 250ft of the blast site. Written confirmation that the pre-blast survey has been done shall be maintained by the blasting contractor. Requests for access to structures for pre-blast surveys shall be made by certified mail to the last known address of the owner (s) of any structures located within the pre-blast survey areas as defined above. If permitted by the owner (s) pre-blast surveys shall be conducted to determine the pre-blast conditions of the structures. A minimum of 14 days' notice shall be provided for the scheduling of the pre-blast survey. Documentation consisting of a written acknowledgment that the survey has been performed or declined by the property owner and a map depicting the above referenced 150 and 250ft radius, shall be provided to the Fire Marshal at the time of site inspection. Depending on circumstances, the Fire Marshal may request additional pre-blast surveys be conducted outside of reference distances.
- The pre-blast shall be conducted at a maximum of 120 days prior to the anticipated initial blast.
- *Pre-blast Notification*. All structures located within 300ft of the blast site shall be notified 48 hours prior to the initial blasting operations and no blasting shall occur until such notice has been given.

Applicant Signature:	Date:
FMO Reviewer:	Date:

NOTICE: Section 5607.16 of the 2021 edition of the Virginia Statewide Fire Prevention Code (SFPC) requires the use of the shot record referred to as "Form 5607.16". The SFPC does allow the blaster in charge to use another format so long as it contains the minimum data and information indicated in Form 5607.16.

This form is a public document and may be printed and used without obtained permission prior to its use.

Virginia Statewide Fire Prevention Code Form 5607.16 Blast (shot) Record

Blo	ock 1	Gene	eral Information				
1	Blast date:	Blast No.:	Blast Time:		Permit No.:		
2	Blast location by address including city, county, or town:						
3	Blast location by GPS of	coordinates:	□check box	if unknown			
4	Name of Permit Holder						
5	Name of Blaster in char	Name of Blaster in charge (print):					
6	Signature of Blaster in o	charge:					
7	Certification Number of	Blaster in charge:					
Blo	ock 2	General env	vironmental cond	itions			
1	Weather (Clear? Cloudy? Overcast?)	Wind dired	ction and speed @mph	Temperatu	re F° / C°		
2	Topography: (Flat? Hilly Mountainous?)	'	rom blast site to habited building:	building de	om nearest inhabited termined by: GPS coordinates Measurement Estimated		
3	Use of nearest inhabite building? (Dwelling? Busin Apartment Building? School?	ess? nearest in	rom blast site to habited building:	inhabited t □ □	om blast site to nearest building determined by: GPS instrument Compass Estimated		
Addit	tional Blaster notations on envir	onmental conditions:		,			

Blo	ock 3	t levent and present	tions taken		
1	No. of holes	t layout and precau Diameter of			oplicable) th of hole(s)
	Were any holes decked? ☐ Yes	How many holes we	re decked?	How m	any decks per hole? □ N/A
2	□ No	(If applicable, indicate on the number of decks for t	any attached shot pa he hole[s].)	ittern draw	ring which holes were decked and
3	Shot pattern	Depth of su	b-drilling	Drilli	ng angle
	☐ Check this box if only single	_			
4	Burden	Spacing of I	noles	Wate	er height
5	Stemming height	Material use	ed for stemming	Chec	
A ddit	ional Blaster notations on shot	t layout and proportions:			☐ Mats
Addit	ional diaster hotations on shot	rayout and precautions.			□ Overburden
					☐ None taken
				•	
Blo	ock 4	Seismic control me	asures (N/A = No	ot Applicab	le)
1	Was Scaled Distance Formula used? □ Yes □ Was Scaled Distance equation was used Distance equation was used Distance equation was used Distance. □ W(lb)=[D(ft)/50]²			Max. Allow. Chg. Wt. per 8 ms based on Scaled Distance. □ N/A	
	□ No	□ W(lb)=[D(ft)	□ W(lb)=[D(ft)/55] ²		
		□ W(lb)=[D(ft)	/65] ²		
2	Was seismograph used? ☐ Yes	Seismograph manufac number: □ N			Seismograph serial number: □ N/A
	□ No				Seismograph's last calibration date. □ N/A
3	Distance and direction site □ N/A		etermine N/A Estimate	☐ GPS coordinates	
4	Seismograph Geophone Minimum F	□ N/A Seismograph recordings: □ N/A			ngs: □ N/A
	Seismograph				
5	Seismograph trigger le			_	dB Hz
	in/s	sdB			
Addit	ional Blaster notations on seis	mic control measures:			

Block 5 Quantity and product						
	Max. Allow. Chg. Wt. per 8 m		Initiation (Ched	:k)		
1		☐ Delay not used	ed Check)			
	lbs					
2	Max. No. of Holes/Decks per	8 ms interval				
2	□ Delay not used □ Elect			☐ Electronic		
	Max. Wt. or sticks of Explosiv	e per hole	Firing device m	nanufacturer and mo	del: □ N/A	
3	lbs					
		Product listing	<u> </u>	pages as needed.)		
4	Manufacturer Prod	uct name, descri	otion or brand	Number of units	Unit weight (lb)	
5		То	tal explosive we	ight in this shot:	lbs.	
Addit	tional Blaster notations on product and	quantities:				
Blo	ock 6					
		on of shot reco	ord and genera	I comments		
Gene	eral comments on shot not included in r					
Date	e shot report completed:	Time shot report	completed:			
Prin	ted name and signature of	(Print)				
pers	son completing shot report if					
diffe	erent from Block 1, Lines 5	(Signature)				
and	U.	, - ,				